

## Side Mount Hydrostatic Fuel/Fresh Water Sensor




- Pressure ranges from 0.1 up to 1000bar
- Isolated construction, able to test various media
- Stainless steel 316L diaphragm
- Vented gauge, sealed gauge and absolute pressure
- Analog PCB, zero/span adjustable
- Piezoresistive pressure sensor, silicone oil filled
- Output signals: 4-20mA and 0-10V, 0-5V voltage output

The Oceanic Systems' Side Mount Hydrostatic Fuel/Fresh Water Sensor works on following the piezoresistive principle and has a standard medium working temperature from -20-100°C.


The sensor adopts a high performance piezoresistive pressure transducer as the sensing part, the inner structure is O-ring sealed and has a 0 to 70°C wide temperature compensation. This sensor is suited for applications in marine environments for sensing pressures ranging from 0,1 to 1000 bar.

# Side Mount Hydrostatic Fuel/Fresh Water Sensor. Part No. 4670(0-2M)-4671(0-4M)

## Dimensions



## Mounting



Electrical connections		
	DIN43650 connection	Cable connection
4-20mA Current output signal (2 wire)	Pin 1: + supply Pin 2: + output Pin 3: Not used Earth: Not connected	Red: + supply Black: + output
0-10V, 0-5V, 0.5-4.5V Voltage output signal (3 wire)	Pin 1: + supply Pin 2: GND Pin 3: + output Earth: Not connected	Red: + supply Black: GND Blue: + output
IP protection (fulfilled together with mating connector)	protection ( fulfilled together with mating connector) IP 65	IP 65

Performance	
Accuracy @25°C (incl. non-linearity, hysteresis and repeatability)	±0.5% F.S.
Non-linearity BFSL (conformity)	≤ ±0.3% F.S.
Hysteresis and repeatability	≤ ±0.1% F.S.
Response time	< 4 ms
Pressure range	0...0.1bar to 1000bar -1...0bar, -1...1bar(negative pressure)
Overload pressure	2.0 × F.S. (≤ 250 bar)
	1.5 × F.S. (> 250 bar)
	1.2 × F.S. (1000bar)
Pressure type	vented gauge, sealed gauge, absolute
Long term stability	≤0.2%F.S./Year
Temperature coefficient	±0.03%F.S./°C

Electrical specifications				
	4-20mA (analog)	0-10V (analog)	0-5V/0.5- 4.5V (analog)	0.5-4.5V (analog)
Supply voltage	12-36Vdc	15-36Vdc	10-36Vdc	5Vdc
Polarity protected	Yes	Yes	Yes	Yes
Short-circuit protected	Yes	Yes	Yes	Yes
Zero and span adjustment	Yes	Yes	Yes	Yes
Surge protection	No	No	No	No

Environmental conditions	
Medium temperature range	-20°C – +100°C
Ambient temperature range (depending on electrical connection)	-20°C – +80°C
Compensated temperature range	-10°C – +70°C
EMC - Emission	EN 61000-6-3
EMC - Immunity	EN 61000-6-1
Insulation resistance	>100 MΩ at 250 V

Mechanical characteristics		
Materials	Diaphragm	Stainless steel 316L
	Enclosure	Stainless steel 304
	Electrical connections	PA66, stainless steel
	O-ring	Viton
Weight (depending on pressure connection and electrical connection)		0.15 - 0.3 kg
Pressure connection	G1/2	
Electrical connection	Direct cable	

Oceanic Systems (UK) Ltd  
Unit 10-11 Milton Business Centre, Wick Drive,  
New Milton, Hampshire, BH25 6RH, United Kingdom

Tel (UK): +44(0)1425 610022  
Fax: +44(0)1425 614794  
Web: www.osukl.com

Tel (USA): (844)898 6462  
Email: sales@osukl.com

Copyright © 2020 Oceanic Systems (UK) Ltd. All rights reserved. Our policy is one of continuous product improvement so product specifications are subject to change without notice. Oceanic Systems products are designed to be accurate and reliable. However, they should be used only as aids to vessel monitoring, and not as a replacement for traditional navigation and vessel monitoring techniques.

NMEA2000® is a registered trademark of the National Marine Electronics Association.