

NMEA2000® AC MONITOR

FEATURES

- ◆ Inputs for AC Voltage (300 VAC MAX)
- ◆ Inputs for 200 Amp AC Current Transformers
- ◆ User Settable Circuit Type
- ◆ Heartbeat LED Confirming NMEA Transmission
- ◆ NMEA2000® Micro-C Interface Plug
- ◆ Robust environmentally protected enclosure and connections
- ◆ The unit reports, AC Voltage, Current, Frequency, Power



The Oceanics Systems 3420 AC Monitor accurately measures the AC Voltage, AC Current, AC Frequency and AC Power and reports them over the NMEA2000® network.

The unit can be used for Single Phase, Two Phase, Three Phase and Split Phase systems and is suitable for measuring AC sources such as shore power, generators and inverters. It can also measure the voltage and frequency on AC Bus Bar Systems.

The voltage sensing is by simple phase and neutral connections to the unit. Current sensing is done by a state of the art AC Current Transformer placed around the conductor with no need to break the connection.

The unit has inputs for up to three phase voltages and up to three phase current transformers. It is supplied with a single

phase current transformer. Additional transformers will be required to measure Two Phase, Three Phase and Split Phase circuits.


The 3420 has a blue LED that flashed as the unit transmits data over the network with configuration done with a suitable Oceanic Systems Display Unit, our Monex PC Software or pre-configuration when ordering direct from Oceanic Systems. Up to 254 units can be present on a single network.

The connections to the sensors are made via a waterproof and corrosion resistant DT15-12PA Deutsch Connector which allows for a secure and reliable connection.

NMEA2000® AC MONITOR

Part Number 3420

Unit Dimensions



3423 200 AMP AC Current Transformer



Design Standards

NMEA2000®	Level B
Maritime Nav and Radio-Comm Equipment	IEC60945
CE and FCC	Electromagnetic Compatibility

NMEA2000® PGNs

Monitor	PGN 127744	AC Power / Current - Phase A
	PGN 127745	AC Power / Current - Phase B
	PGN 127746	AC Power / Current - Phase C
	PGN 127747	AC Voltage / Frequency - Phase A
	PGN 127748	AC Voltage / Frequency - Phase B
Protocol	PGN 127749	AC Voltage / Frequency - Phase C
	PGN126464	Tx/Rx PGN List
	PGN126996	Product Information
	PGN126998	Configuration Information
	PGN059392	ISO Acknowledgement
	PGN059904	ISO Request
	PGN060928	ISO Address Claim
	PGN126208	Command/Request Group
	PGN126993	Transmit Heartbeat

Electrical and Mechanical

Operating Voltage	9 to 28 Volts	DC Voltage
Power Consumption	30mA	Average Operating
Load Equivalence Number	1	LEN
Reverse Battery Protection	Yes	Indefinitely
Load Dump Protection	Yes	SAE J1113
Size	mm	123 x 104 x 47
Weight	gr	120

Environmental

IEC 60954 Classification	Protected
Degree of Protection	IP40
Operating Temperature	-25°C to 50°C
Storage Temperature	-40°C to 70°C
Relative Humidity	93%RH @40° per IEC60945-8.2
Vibration	2-13.2Hz @ ±1mm, 13.2-100Hz @ 7m/s2 per IEC 60945-8.7
Electromagnetic Emission	Conducted and Radiated Emission per IEC 60945-9
Electromagnetic Immunity	Conducted, Radiated, Supply, and ESD per IEC 60945-10
Safety Precautions	Dangerous Voltage, Electromagnetic Radio Frequency per IEC 60945-12

Oceanic Systems (UK) Ltd

Unit 10-11 Milton Business Centre, Wick Drive, New Milton, Hampshire, BH25 6RH, United Kingdom

Tel (UK): +44(0) 1425 610022 Tel (USA): (844) 898 6462
 Fax: +44(0)1425 614794 Email: sales@osukl.com
 Web: www.osukl.com

Copyright © 2021 Oceanic Systems (UK) Ltd. All rights reserved.

Our policy is one of continuous product improvement, therefore product specifications are subject to change without notice. Oceanic Systems products are designed to be accurate and reliable. However, they should be used only as aids to vessel monitoring, and not as a replacement for traditional navigation and vessel monitoring techniques.

NMEA2000® is a registered trademark of the National Marine Electronics Association.