


POSEIDON® 19 19" INTEGRATED MONITORING AND CONTROL SYSTEM

FEATURES

- ◆ Monitor, display and control ships data
- ◆ NMEA2000® certified
- ◆ Breathtaking vector graphics
- ◆ High resolution, sunlight readable, touchscreen display
- ◆ Fully customisable interface
- ◆ IP66 for all-weather use




Poseidon 19 offers both sail and power boats the ability to monitor and control any vessel data and display it effortlessly on the small, yet powerful display unit.

Ideal for 25-60ft vessels of all types, the NMEA2000® certified 19" integrated monitoring and control system monitors and controls any systems from tank levels, engines, AC and DC power and digital switching, bilge and fire detection systems, and all other vessel systems with ease.

Poseidon® 19 - 19" Integrated Monitoring and Control System

Part Number: 5200



Design Standard

NMEA2000	Level B
----------	---------

NMEA2000® Parameter Group Numbers (PGNs)

Type	PGN No.	PGN Name	Default rate
Periodic data PGNs	PGN126993	Heartbeat	60s
Response to requested PGNs	PGN131009	Channel Status (proprietary)	N/A
	PGN126464	PGN List (Transmit and Receive)	N/A
	PGN126996	Product Information	N/A
	PGN126998	Configuration Information	N/A
Protocol PGNs	PGN059392	ISO Acknowledge	N/A
	PGN059904	ISO Request	N/A
	PGN060928	ISO Address Claim	N/A
	PGN065240	ISO Address Command	N/A
	PGN126208	Complex Command	N/A

Electrical and Mechanical

Parameter	Value
Operating Voltage	9 to 32 VDC
Power Consumption	500mA @24V (average operating)
CAN Voltage	9 to 32 Volts
Load Equivalence No.	1
Size	508 x 132 x 53.5mm
Weight	TBA
Connectors	NMEA2000® - Sealed M12 Micro-C
	USB - Sealed
	Ethernet - Sealed
	Power - Sealed 2 Pin

Environmental

Parameter	Value
IEC60954 Classification	Protected
Degree of Protection	IP66
Operating Temperature	-20°C to 50°C
Storage Temperature	-30°C to 70°C
Relative Humidity	93%RH @40° per IEC60945-8.2
Vibration	2-13.2Hz @ ±1mm, 13.2-100Hz @ 7m/s2 per IEC60945-8.7
Electromagnetic Emission	Conducted and Radiated Emission per IEC60945-9
Electromagnetic Immunity	Conducted, Radiated, Supply, and ESD per IEC60945-10

Oceanic Systems is a brand of:

Energy Solutions UK Ltd, Broadmead House,
Bellingham Way, Aylesford, Kent, ME20 6XS

+44 (0)1634 290772 sales@energy-solutions.co.uk
energy-solutions.co.uk

Revision 02. Copyright © 2026 Energy Solutions UK Ltd. All rights reserved.

Our policy is one of continuous product improvement, therefore product specifications are subject to change without notice. Oceanic Systems products are designed to be accurate and reliable. However, they should be used only as aids to vessel monitoring, and not as a replacement for traditional navigation and vessel monitoring techniques.

NMEA2000® is a registered trademark of the National Marine Electronics Association